# **Technical Data Sheet**

**Product** 

Model: AB-3052

**Description:** Retrofit-gable style solar powered attic fan constructed from corrosion resistant


zincalume alloy steel featuring a 14 inch diameter fan blade, remote mounted 30W solar panel with standard flush mounting brackets, 15 foot UV/weather-resistant power cable,

stainless steel hardware throughout, and thermal switch control included.


Revision: 0

**Date:** 4/1/2017 **DCN:** TDS-3052


#### **TOP VIEW**




#### **BOTTOM VIEW**



### SIDE VIEW





19.69 in (500 mm)

## **Technical Data Sheet**

**Materials** 

Hood & Base: 22 GA (0.027 in; 0.686 mm) Zincalume/Galvalume AZ50 (ASTM A792)

Support Brackets: N/A

Motor Brackets: 16 GA (0.058 in; 1.473 mm) 304 Stainless Steel (ASTM A666)

Wildlife Screen: N/A

Hardware & Fasteners: 1/4" 18-8 Stainless Steel

Fan Blade: 16 GA (0.050 in; 1.270 mm) Aluminum AL5052 (ASTM B209); 14 in (356 mm) diameter,

5-wing precision balanced blade

PV Panel: AL5052 aluminum frame with impact-resistant tempered glass; AL5052 aluminum

standard mounting brackets (available with adjustable universal bracket kit)

**Finish** 

N/A **Coating Type: Coating Thickness:** N/A Adhesion: N/A **Exposure Performance:** N/A **Corrosion Resistance:** N/A **Certifications:** N/A **Stock Colors:** N/A **Custom Colors:** N/A

**Electrical** 

**Motor:** 38V variable speed DC motor with sealed bearings; fully enclosed and designed to be

intrinsically safe with overload protection

PV Panel: High efficiency 30 watt panel; monocrystalline solar cells

Internal Wiring: 16/18 AWG wiring throughout unit

Remote Cable: 18 AWG UV/weather resistant power cable (15 feet); available with 14 AWG extended

power cable (40 feet)

**Termination:** UV/weather resistant quick disconnect plugs

Fan Control: Thermal switch included (activates 75°F ± 7°F, deactivates 55°F ± 9°F - UL 873

compliant); Breeze Mate® solar ventilation control system optional

**Performance** 

Max Airflow Rating: 1700 CFM @ 0.0 inH2O under peak sun exposure

Noise Level: < 1 sones (< 30 dB)

Wind Rating: N/A
Certifications: N/A

Warranty: Residential limited Lifetime Warranty; commercial 25-year limited warranty

Weight Load

**Fan Unit:** 9 LBS **Remote PV Panel:** 5 LBS

